

# LANDOCOL

## the fast and clean method of laying textile floor covers

### APPLICATION

On smooth utility covers such as lino and parquet floors (which are no longer used in their original state), and on timber, concrete, needle felt and non-porous stone floors.

- Carpets adhere like glued and are wheel chair resistant subject to a suitable top material
- Recommended for floor heating
- Enhances walking comfort
- Improves step sound absorption
- Free of plasticizer, is non-ageing and non-rotting
- Carpets remain easily removable

**NOT SUITABLE for laying on floors with a high plasticizer content such as e.g. PVC and porous stone floors (marble, clay tiles, etc.)**

### LAYING

- The floors must be free of dust, wax and grease
- To be laid at room temperature if possible
- Porous substrates and particle boards must be primed
- Additional fixation of the seams with double-sided adhesive tape or, alternatively, welding of the seams with suitable making-up tape, is recommended in any case.

**Depending on the duration and the load applied while laying a floor cover with LANDOCOL, more or less residues of adhesive will remain on the substrate or the old utility cover.**

**Removal of adhesive residues:** INTENSIVE CLEANER 75-27 neutral  
INTENSIVE CLEANER-SPECIAL 75-34 neutral

CHEDDITE-TRADING LTD, CH-6456 ISLETEN (Phone 041 / 878 11 66)

**Unit weight:** approx. 180 g/m<sup>2</sup>

**Thickness:** approx. 2.0 mm

**Heat conductivity  $\lambda$ :** approx. 0.038 W/m·K

**Thermal resistance R:** approx. 0.053 m<sup>2</sup>·K/W

**Delivery form:** **Rolls of**  
length: 27.8 m  
width: 90 cm  
diameter approx.: 27 cm

As the working conditions and the multitude of different materials are outside our influence, no legal claim can be derived from the information provided by us. We recommend to carry out adequate own testing.  
The recommendations made by the producers of the covers should be adhered to in any case.

er: 06.02