


Technical data Floorliner™

Product type

Floorliner™ original



Multifunctional protective nonwoven
 with adhesive coating OPTICOAT™ by Landolt

Characteristic properties

Material

Nonwoven of synthetic fibres
 Top side with PE sheet acting as barrier against liquids

Rear side with slip resistant coating OPTICOAT™ by Landolt

Colour

white

Technical properties

Unit weight

approx. 180 g/m²

Thickness

approx. 2.0 mm

Water vapor permeability

-

Water imper-meability

-

Water absorption ability

-

Advantages

Protects floors, carpets, stairs, tiles, etc (E.g. from mechanical damage or stains from spilled liquids)

Helps to prevent accidents (Rear side with active protection against slipping)

Can be used several times, quickly laid out (Cost saving)

Environment-friendly (Free of harmful substances, thermally disposable)

Important

Floorliner™ is not suitable for newly laid floors, porous stone floors and clay tiles.

Laying

with overlap of 10 cm

Delivery form rolls of

Length

50 m


Width

100 / 200 cm

Diameter approx.

37 cm

Function / Application



Safe and highly effective protection of floors of all kinds, carpets, tiles, furniture, etc.



The values given are average obtained according to internal and external testing. We reserve the right to make changes at any time in accordance with our knowledge, technology and experiences without any notice.