


Technical data Floorliner™ FR

Product type

Floorliner™ FR



Multifunctional, hardly combustible protective nonwoven with adhesive coating
 OPTICOAT™ by Landolt

Characteristic properties

Material

Nonwoven of flame retardant synthetic fibres
 Top side with PE sheet acting as barrier against liquids

Rear side with slip resistant coating OPTICOAT™ by Landolt

Colour

green

Technical properties

Unit weight

approx. 210 g/m²

Thickness

approx. 2.0 mm

Fire code numbers

BKZ 5.1 / DIN 4102-B1 / Large flame test to LPS 1207

Advantages

Helps to prevent accidents (Rear side with active protection against slipping)
 Environment-friendly (Free of harmful substances, thermally disposable)

Protects floors, carpets, stairs, tiles, etc (E.g. from mechanical damage or stains from spilled liquids)
 Can be used several times, quickly laid out
 (Cost saving)

Important

Floorliner™ FR is not suitable for newly laid floors, porous stone floors and clay tiles.

Laying

with overlap of 10 cm

Delivery form Rolls of

Length

50 m


Width

100 / 200 cm

Diameter approx.

40 cm

Function / Application



Provides safe and effective protection. Serves to cover floors of all types, carpets, tiles, furniture, etc.



The values given are average obtained according to internal and external testing. We reserve the right to make changes at any in accordance with our knowledge, technology and experiences without any notice.