


## Technical data Floorliner™ absorb

### Product type

**Floorliner™ absorb**



Multifunctional protective nonwoven with OPTICOAT™ adhesive coating by Landolt – safely absorbs paint and other liquids.

### Characteristic properties

Material

Nonwoven of synthetic fibres  
 Absorbent top sandwich with impermeable barrier

Rear side with slip resistant coating OPTICOAT™ by Landolt

Colour

white

### Technical properties

Unit weight

approx. 205 g/m<sup>2</sup>

Thickness

approx. 2.2 mm

Water vapor permeability

-

Water impermeability

-

Water absorption ability

450 g/m<sup>2</sup>

### Advantages

Protects floors, carpets, stairs, tiles, etc (E.g. from mechanical damage or stains from spilled liquids)

Helps to prevent accidents (Rear side with active protection against slipping)

Can be used several times, quickly laid out (Cost saving)

Environment-friendly (Free of harmful substances, thermally disposable)

Absorbs liquids reliably

### Important

Floorliner™ absorb is not suitable for newly laid floors, porous stone floors and clay tiles.

### Laying

with overlap of 10 cm

### Delivery form rolls of

Length

50 m


Width

100 / 200 cm

Diameter approx.

37 cm

### Function / Application



Save and highly effective protection of floors of all kinds, carpets, tiles, furniture, etc. Absorbs reliably liquids and stops them soaking through to the protected surface below.



The values given are average obtained according to internal and external testing. We reserve the right to make changes at any time in accordance with our knowledge, technology and experiences without any notice.